

Side By Innovations

Switch Plate Installation Instructions

- Step 1. Remove the headlight switch, the 4WD switch and the 12 volt accessory plug from the RZR dash. You will need to re-locate the accessory plug for this installation.

- Step 2. Use scissors to cut the outside profile of this template. Do not cut inside pocket at this time.

- Step 3. Peel off the backing and carefully stick the template in position on the RZR dash. Make sure the template is straight and in the location that you want the switch plate to end up. Note: *The factory switch pockets may not line up in the locations shown on the template. Those are there for reference only and are approximate.*

- Step 4. Center punch and drill three 3/16" diameter mounting holes in locations shown on template.

- Step 5. Center punch and drill 3/8" diameter holes in three corners of the shaded pocket as shown on template.

- Step 6. Remove the shaded area using a controllable and accurate cutting device such as a Dremel tool with a slitting disc to cut through the plastic along the straight sides of the shaded pocket. Stay just inside the lines around the shaded area, be very careful not to cut past the outside line of the template

- Step 7. Peel off the remaining part of the template, de-burr the pocket with a file and install the switch plate. Secure plate with three supplied 8-32 screws from the back side through the three mounting holes.

- Step 8. Install switches by pushing them straight into the rectangular pockets. If they are too tight, push the butterfly tabs down a little before installing.